



# DRITEL FREE STANDING 3G SERIES 7

LOUD SPEAKING TELEPHONE

## TECHNICAL SPECIFICATIONS:

<b>Working Frequency Range</b>	WCDMA850/1900/2100MHz GSM850/900/1800/1900MHz
<b>Operating Voltage</b>	7.4V-12V
<b>Idle Current</b>	7mA
<b>Off Hook Current</b>	78mA

Each unit can be simply programmed or reprogrammed from any location. The Unit will send a confirmation "SMS" of the new numbers programmed into the Unit.



## AUTOMATIC DIAGNOSTIC REPORTING:

Unit will automatically send a message when at least one of the following conditions occurs:

- 1 Battery State below 11.8V
- 2 Faulty switch or keypad
- 3 Led Indicator Condition

## MANUAL FAULT DIAGNOSIS:

Upon requesting a Fault Diagnosis from the phone, the following information will be sent in the form of an "SMS" report.

- ✓ Signal Status
- ✓ Battery Status
- ✓ Keypad/Switch status
- ✓ Indicator Light condition
- ✓ Preprogrammed number of the unit
- ✓ Preprogrammed SMS reporting number

## POWER SPECIFICATIONS:

15W Solar Panel



LifePO4 12.8V, 12Ah Battery

## OPTIONS:



- Can be fitted with an external light
- CCTV
- Height can be optional
- Higher wattage solar panels
- Larger batteries can be included
- Colour choices
- Hotline version or keypad style
- Ground, wall, barrier mounting
- Remote 12V power source
- Customized construction

## ENGINEERING SPECIFICATIONS:

<b>Casing Material</b>	Marine Grade Aluminium, 316 Stainless Steel fittings.
<b>Finish</b>	UV Rated Powder Coating. Standard colour blue
<b>Fittings</b>	316 Grade Stainless Steel
<b>Total Height</b>	2.6m (Height optional)
<b>Weight</b>	15 kg
<b>Phone Case maximum dimensions</b>	460mm High x 230mm Wide x 160mm Deep
<b>Pole Diameter</b>	100mm
<b>Built in four main sections</b>	Lower Pole, Phone Unit, Upper Pole, Solar panel assembly
<b>Designed to be assembled and installed by one person within 20 minutes</b>	
<b>Highly Vandal Resistant</b>	
<b>IP 65 Rating</b>	